# **PIPISTRELLO-MED**


code: 620/MED/DIM/BI







TABLE LAMP, DIFFUSED LIGHT, ADJUSTABLE HEIGHT. GLAZED STAINLESS STEEL TELESCOPE. WHITE OPAL METHACRYLATE DIFFUSER. BASE AND KNOB: DARK BROWN OR WHITE, WITH LED LIGHT SOURCE. DIMMABLE. ELECTRONIC DRIVER ON THE PLUG.

## **TECHNICAL DRAWINGS**







**UTILIZATION: INTERNAL** TYPOLOGY: **TABLE LAMPS COLOURS** STRUCTURE: WHITE DIFFUSER: WHITE STRUCTURE: STAINLESS STEEL MATERIALS DIFFUSER: **OPAL WHITE METHACRYLATE MEASURES** WIDTH: -DIAMETER: 40 cm WEIGHT NET: -HEIGHT: 50-62 cm GROSS: -HOLE DIAMETER: -LENGTH: -HOLE DEPTH: -DEPTH: -PACKAGING VOL.M3: -NUMBER OF ITEMS: 1 BULBS LED 1X9W FLUX: 850LM KELVIN: 2700° CLASS: A++



CRI: -

COLOR TOLERANCE: -**DURATION: -**

## **DEVICE SPECIFICATIONS**

TYPE OF EMISSION: DIFFUSED POWER: 10 W FLOW LAMP: 787 Im BEAM ANGLE: -DEVICE EFFICIENCY: 78.7Im/W IMPACT RESISTENCE: -

POWER SUPPLY CABLE LENGTH: 35+200cm LENGTH OF HANGING CABLE: -SUPPLY: INCLUDED

POWER SUPPLY ASSEMBLY: EXTERNAL TYPE OF DIMMING: DIMMER ON CABLE

VOLTAGE: 230 V

POWER SUPPLY: ELECTRONIC DIMMABLE POWER SUPPLY

GLOW WIRE TEST: -







MARKETS THIS ITEM IS AVAILABLE IN THE FOLLOWING COUNTRIES:

**EUROPE** 



**PIPISTRELLO-MED** 

code: 620/MED/DIM/BI

PHOTO GALLERY











# martinelli luce


# **PIPISTRELLO-MED**


code: 620/MED/DIM/MA




TABLE LAMP, DIFFUSED LIGHT, ADJUSTABLE HEIGHT. GLAZED STAINLESS STEEL TELESCOPE. WHITE OPAL METHACRYLATE DIFFUSER. BASE AND KNOB: DARK BROWN OR WHITE, WITH LED LIGHT SOURCE. DIMMABLE. ELECTRONIC DRIVER ON THE PLUG.

## **TECHNICAL DRAWINGS**







**DESIGN GAE AULENTI** 1965

UTILIZATION: INTERNAL

TYPOLOGY: **TABLE LAMPS** 



**COLOURS** STRUCTURE: **DARK BROWN** 

DIFFUSER: WHITE

STRUCTURE: STAINLESS STEEL MATERIALS

> DIFFUSER: **OPAL WHITE METHACRYLATE**

**MEASURES** WIDTH: -DIAMETER: 40 cm WEIGHT NET: -GROSS: -

HEIGHT: 50-62 cm HOLE DIAMETER: -LENGTH: -HOLE DEPTH: -

DEPTH: -

PACKAGING VOL.M3: -NUMBER OF ITEMS: 1

BULBS LED 1X9W

> FLUX: 850LM KELVIN: 2700° CLASS: A++ CRI: -

COLOR TOLERANCE: -

**DURATION: -**



## **DEVICE SPECIFICATIONS**

TYPE OF EMISSION: DIFFUSED POWER: 10 W

FLOW LAMP: 787 Im BEAM ANGLE: -

DEVICE EFFICIENCY: 78.7Im/W

IMPACT RESISTENCE: -

GLOW WIRE TEST: -

POWER SUPPLY CABLE LENGTH: 35+200cm

LENGTH OF HANGING CABLE: -

SUPPLY: INCLUDED

POWER SUPPLY ASSEMBLY: EXTERNAL TYPE OF DIMMING: DIMMER ON CABLE

VOLTAGE: 230 V

POWER SUPPLY: ELECTRONIC DIMMABLE POWER SUPPLY

MARKETS





THIS ITEM IS AVAILABLE IN THE FOLLOWING COUNTRIES:

**EUROPE** 



**PIPISTRELLO-MED** 

code: 620/MED/DIM/MA

DESIGN GAE AULENTI 1965

PHOTO GALLERY









