Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or	trade mark:	Vibia
--------------------	-------------	-------

Supplier's address: Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

Model identifier: 027011/12

T	- 6	10 - 1- 1	
IVno	α T	IIσnt	CULILCO.
IVDC	vı	IIGIIL	source:

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	o-type	Renobable PCB		
(or other electri	ic interface)			
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	9	Energy efficiency class	E
dicating if it refe a sphere (360°)	s flux (фuse), iners to the flux in , in a wide cone arrow cone (90º)	1 093 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P _{on}), ex-	9,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,10
(P_{net}) for CLS, ϵ	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimen-	Height	300	Spectral power dis-	See image
المطاهلين ممتملم	1	1	1 4 mile - 4 mile - 1 mile - 1 mile - 1	· · · · · · · · · · · · · · · · · · ·

1 730

2 000

tribution in the

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,456	
		nates (x and y)	0,413	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	54	Survival factor	-	
the lumen maintenance factor	-			

(a)'-': not applicable; (b)'-': not applicable;

